

AUTO ZOOM

SCADSG30X

General Features :



Model NO.	SCADSG30XHA	SCADSG30XA130	SCADSG30XE200
Camera			
Category	Analogue Camera	HD Camera	IP Camera
CCD/CMOS	CCD	CMOS	CMOS
Image Sensor	ICX811AK	IMX238	IMX238
DSP	Effio-A	2431H	A5S66



Horizontal Resolution	720TVL	1.4MP	3MP	
Effective Pixels	976(H)×582(V)	1280(H)×960(V)	1280(H)×960(V)	
TV System	PAL/NTSC			
Electronic Shutter Time	Auto: PAL 1/50-1/100, 000Sec; NTSC 1/60-1/100, 000Sec	1/25s~1/50,000s , 1/30s~1/60,000s	Auto: PAL 1/1-1/10000Sec; NTSC 1/1-1/10000Sec	
Sync System	Internal		External	
Usable Illumination	0.001Lux/F2.0	0.001Lux/F2.0	0.001Lux/F2.0	
S/N Ratio	≥50dB	≥50dB	≥52dB	
Gamma Correction	0.45			
Scanning System	PAL:625 Lines, 50 Field/Sec;NTSC:525 Lines, 60 Field/Sec	Progressive Scan	Progressive Scan	
Video Output	Composite Signal (1.0Vp-p, 75Ω)	AHD/CVBS (960H) (BNC)	Network	
Lens				
Focus Length	2.8-12mm			
Focus Control	Auto			
Lens Type	Auto			
Pixels	2M Pixels			
Auto Iris Support	Auto			
Night Vision				



Infrared LED	Φ 5X36PCS		
Infrared Distance	30M		
IR Status	Under 10 Lux By CDS		
IR Power On	CDS Auto Control		
Camera Features			
Day/Night	Color/ B&W	Auto (ICR) / Color / B&W	Color/ B&W (IR-CUT)
OSD Menu Language	CN, EN, FR, DE, JP, ES, PT, RU	EN, CN, DE, FRA, IT, ES PL, RU, PT, NL, TR	CN,EN,BG,PL,FA,DE,RU FR,KO,PT,JA,TR,ES,HE,IT
Defog	YES	NO	NO
Sense-up	YES	YES	YES
Smart-IR	YES	NO	YES
Wide Dynamic Range	Super DWDR	DWDR	WDR
Backlight Compensation	YES	NO	NO
White Balance	AUTO	AUTO	AUTO
Gain Control	AUTO	AUTO	AUTO
Noise Reduction	3D NR	3D NR	3D NR
Privacy Masking	YES	NO	NO
Digital Zoom	NO	NO	YES



Picture Adjustment	YES	YES	YES
UTC Support	YES	NO	NO
General			
Vandalproof Housing	YES		
Weatherproof Housing	NO		
Lens Angle Adjustment	YES		
Dual Voltage	NO		
IR Cut Filter	NO		
Heater	NO		
Operation Temperature	-10°C ~ +50°C RH95% Max		
Storage Temperature	-20°C ~ +60°C RH95% Max		
Power Source	DC12V±10%,700mA		
Dimension	125(W) x 105.8(H) x 135(D) mm		
Weight	800g		

