

BULLET AHD/CVI/TVI

SCAVB40

General Features :

IR Bullet IP66, 2.8-12mm Varifocal Lens, 40m Night Vision

⌘ 5X42PCS



Model N O.	SCAVB40 A100	SCAVB40 A130	SCAVB40 A200M	SCAVB40 A200H	SCAVB4 0C130L	SCAVB40 C130M	SCAVB40 C130H	SCAVB40 C200M	SCAVB40 C200H	SCAVB40 V130M	SCAVB40 V130H	SCAVB40 V130	SCAVB40 V200M	SCAVB40V200 H
Video Ou tput Mod e	AHD/CV BS	AHD/CVB S	AHD/CVB S	AHD/CVB S	CVI/CV BS	CVI	CVI/CVBS	CVI	CVI	TVI/CVBS	TVI/CVBS	TVI	TVI	TVI
Camera														
Image Sen sor	OV9712S	IMX225	OV2710	IMX322	OV9750	AR0130	IMX225	OV2710	IMX322	OV9750	IMX225	IMX238	OV2710	IMX322
DSP	NVP2431 H	NVP2431H	NVP2441H	NVP2441H	HTC960	FH8521+D H9801	HTC960	FH8530C	FH8530C	HTC960	HTC960	FH8521+TP 2801	FH8531+TP 2801	FH8531+TP2801
Image Res olution	720P/960 H	960P/960H	1080P/960 H	1080P/960 H	960P/960 H	960P	960P/960H	1080P	1080P	960P/960H	960P/960H	960P	1080P(960 H)	1080P(960H)
Effective P ixels	1.0MP, 12 80x720	1.3MP, 128 0x960	2.1MP, 192 0x1080	2.4MP, 192 0x1080	1.3MP, 1 280x960	1.3MP, 128 0x960	1.3MP, 128 0x960	2.1MP, 192 0x1080	2.4MP, 192 0x1080	1.3MP, 128 0x960	1.3MP, 128 0x960	1.4MP, 128 0x960	2.1MP, 192 0x1080	2.4MP, 1920x10 80
TV System	PAL/NTSC													
Electroni c Shutter	1/25s~1/50,000s , 1/30s~1/60,000s													
Sync Syste m	Internal													
Usable Illu mination	0.01Lux	0.005Lux	0.001Lux	0.001Lux	0.01Lux	0.01Lux	0.005Lux	0.01Lux	0.01Lux	0.01Lux	0.005Lux	0.001Lux	0.01Lux	0.01Lux
S/N Ratio	≥50dB													
Scanning S	Progressive Scan													



ystem															
Lens															
Focus Length	2.8-12mm														
Focus Control	Manual														
Lens Type	Manual														
Pixels	2M Pixels														
Auto Iris Support	NO														
Night Vision															
Infrared LED	Φ 5X42PCS														
Infrared Distance	40M														
IR Status	Under 10 Lux by CDS														
IR Power On	CDS Auto Control														
Camera Features															
Day/Night	Auto (ICR) / Color / B&W	Auto (ICR) / Color / B&W	Auto (ICR) / Color / B&W	Auto (ICR) / Color / B&W	Auto (ICR) / Color / B&W	Auto (ICR) / Color / B&W	Auto (ICR) / Color / B&W	Auto (ICR) / Color / B&W	Auto (ICR) / Color / B&W	Auto (ICR) / Color / B&W	Auto (ICR) / Color / B&W	Auto (ICR) / Color / B&W	Auto (ICR) / Color / B&W	Auto (ICR) / Color / B&W	Auto (ICR) / Color / B&W
OSD Menu Language	EN, CN, DE, FRA, IT, ES, PL, RU, PT, NL, TR	EN, CN, DE, FRA, IT, ES, PL, RU, PT, NL, TR	EN, CN, DE, FRA, IT, ES, PL, RU, PT, NL, TR	EN, CN, DE, FRA, IT, ES, PL, RU, PT, NL, TR	NO	NO	NO	NO	NO	NO	NO	NO	NO	NO	NO

White Balance	Auto/Manual	Auto/Manual	Auto/Manual	Auto/Manual	Auto	Auto	Auto	Auto	Auto	Auto	Auto	Auto	Auto	Auto
Gain Control	Auto	Auto	Auto	Auto	Auto	Auto	Auto	Auto	Auto	Auto	Auto	Auto	Auto	Auto
Noise Reduction	3D NR	3D NR	3D NR	3D NR	2D NR	3D NR	2D NR	2D NR	2D NR	2D NR	2D NR	3D NR	2D NR	2D NR
Picture Adjustment	YES	YES	YES	YES	NO	YES	NO	YES	YES	NO	NO	NO	YES	YES
WDR	DWDR	DWDR	DWDR	DWDR	NO	WDR	NO	WDR	WDR	NO	NO	NO	WDR	WDR
OSD Support	YES	YES	YES	YES	NO	NO	NO	NO	NO	NO	NO	No	Optional	Optional

General

Weatherproof Housing	YES, IP66
Anti-cut Bracket	YES, 3-Axis
Dual Voltage	NO
IR Cut Filter	YES
Heater	NO
Operation Temperature	-10°C ~ +50°C RH95% Max
Storage Temperature	-20°C ~ +60°C RH95% Max
Power Source	DC12V±10%, 700mA
Dimension	220(W)x80(H)x80(D)mm
Weight	1.4Kg