

BULLET AHD/CVI/TVI

SCAVHC20

General Features :





Model N O.	SCAVHC2 0A100	SCAVHC2 0A130	SCAVHC2 0A200M	SCAVHC2 0A200H	SCAVHC 20C130L	SCAVHC2 0C130M	SCAVHC2 0C130H	SCAVHC2 0C200M	SCAVHC2 0C200H	SCAVHC2 0V130M	SCAVHC2 0V130H	SCAVHC2 0V130	SCAVHC2 0V200M	SCAVHC20V20 0H
Video Ou tput Mod e	AHD/CV BS	AHD/CVB S	AHD/CVB S	AHD/CVB S	CVI/CV BS	CVI	CVI/CVBS	CVI	CVI	TVI/CVBS	TVI/CVBS	TVI	TVI	TVI
Camera														
Image Sen sor	OV9712S	IMX225	OV2710	IMX322	OV9750	AR0130	IMX225	OV2710	IMX322	OV9750	IMX225	IMX238	OV2710	IMX322
DSP	NVP2431 H	NVP2431H	NVP2441H	NVP2441H	HTC960	FH8521+D H9801	HTC960	FH8530C	FH8530C	HTC960	HTC960	FH8521+TP 2801	FH8531+TP 2801	FH8531+TP2801
Image Res olution	720P/960 H	960P/960H	1080P/960 H	1080P/960 H	960P/960 H	960P	960P/960H	1080P	1080P	960P/960H	960P/960H	960P	1080P(960 H)	1080P(960H)
Effective P ixels	1.0MP, 12 80x720	1.3MP, 128 0x960	2.1MP, 192 0x1080	2.4MP, 192 0x1080	1.3MP, 1 280x960	1.3MP, 128 0x960	1.3MP, 128 0x960	2.1MP, 192 0x1080	2.4MP, 192 0x1080	1.3MP, 128 0x960	1.3MP, 128 0x960	1.4MP, 128 0x960	2.1MP, 192 0x1080	2.4MP, 1920x10 80
TV System		PAL/NTSC												
Electronic Shutter		1/25s~1/50,000s , 1/30s~1/60,000s												
Sync System		Internal												
Usable Illu mination	0.01Lux	0.005Lux	0.001Lux	0.001Lux	0.01Lux	0.01Lux	0.005Lux	0.01Lux	0.01Lux	0.01Lux	0.005Lux	0.001Lux	0.01Lux	0.01Lux
S/N Ratio		≥50dB												
Scanning System		Progressive Scan												
Lens														
Focus Length		Board Lens 3.6mm/F2.0												





Focus Control	Fixed
Lens Type	Fixed
Pixels	2M Pixels
Auto Iris Support	NO

Night Vision

Infrared LED	Φ 5X24PCS
Infrared Distance	20M
IR Status	Under 10 Lux by CDS
IR Power On	CDS Auto Control

Camera Features

Day/Night	Auto (ICR) / Color / B&W	Auto (ICR) / Color / B&W	Auto (ICR) / Color / B&W	Auto (ICR) / Color / B&W	Auto (ICR) / Color / B&W	Auto (ICR) / Color / B&W	Auto (ICR) / Color / B&W	Auto (ICR) / Color / B&W	Auto (ICR) / Color / B&W	Auto (ICR) / Color / B&W	Auto (ICR) / Color / B&W	Auto (ICR) / Color / B&W	Auto (ICR) / Color / B&W	Auto (ICR) / Color / B&W
OSD Menu Language	EN, CN, DE, FRA, IT, ES, PL, RU, PT, NL, TR	EN, CN, DE, FRA, IT, ES, PL, RU, PT, NL, TR	EN, CN, DE, FRA, IT, ES, PL, RU, PT, NL, TR	EN, CN, DE, FRA, IT, ES, PL, RU, PT, NL, TR	NO	NO	NO	NO	NO	NO	NO	NO	NO	NO
White Balance	Auto/Manual	Auto/Manual	Auto/Manual	Auto/Manual	Auto	Auto	Auto	Auto	Auto	Auto	Auto	Auto	Auto	Auto
Gain Control	Auto	Auto	Auto	Auto	Auto	Auto	Auto	Auto	Auto	Auto	Auto	Auto	Auto	Auto
Noise Reduction	3D NR	3D NR	3D NR	3D NR	2D NR	3D NR	2D NR	2D NR	2D NR	2D NR	2D NR	2D NR	3D NR	2D NR



Picture Adjustment	YES	YES	YES	YES	NO	YES	NO	YES	YES	NO	NO	NO	YES	YES
WDR	DWDR	DWDR	DWDR	DWDR	NO	WDR	NO	WDR	WDR	NO	NO	NO	WDR	WDR
OSD Support	YES	YES	YES	YES	NO	NO	NO	NO	NO	NO	NO	No	Optional	Optional

General														
Weatherproof Housing	YES, IP66													
Anti-cut Bracket	YES, 3-Axis													
Dual Voltage	NO													
IR Cut Filter	YES													
Heater	NO													
Operation Temperature	-10°C ~ +50°C RH95% Max													
Storage Temperature	-20°C ~ +60°C RH95% Max													
Power Source	DC12V±10%, 500mA													
Dimension	175(W) x 66(H) x 66(Dmm)													
Weight	800g													