


BULLET AHD/CVI/TVI

SCAVK20

General Features :

IR Bullet AHD/CVI/TVI

3.6mm/20M/720P





Model NO.	SCAVK20A100	SCAVK20A130	SCAVK20A200M	SCAVK20A200H
Video Output Mode	AHD/CVBS	AHD/CVBS	AHD/CVBS	AHD/CVBS
Camera				
Image Sensor	OV9712S	IMX225	OV2710	IMX322
DSP	NVP2431H	NVP2431H	NVP2441H	NVP2441H
Image Resolution	720P/960H	960P/960H	1080P/960H	1080P/960H
Effective Pixels	1.0MP, 1280x720	1.3MP, 1280x960	2.1MP, 1920x1080	2.4MP, 1920x1080
TV System	PAL/NTSC			
Electronic Shutter	1/25s~1/50,000s , 1/30s~1/60,000s			
Sync System	Internal			
Usable Illumination	0.01Lux	0.005Lux	0.001Lux	0.001Lux
S/N Ratio	≥50dB			
Scanning System	Progressive Scan			
Lens				



Focus Length	Board Lens 3.6mm/F2.0
Focus Control	Fixed
Lens Type	Fixed
Pixels	2M Pixels
Auto Iris Support	NO

Night Vision

Infrared LED	¢ 5X24PCS
Infrared Distance	20M
IR Status	Under 10 Lux by CDS
IR Power On	CDS Auto Control

Camera Features

Day/Night	Auto (ICR) / Color / B&W	Auto (ICR) / Color / B&W	Auto (ICR) / Color / B&W	Auto (ICR) / Color / B&W
OSD Menu Language	EN, CN, DE, FRA, IT, ES PL, RU, PT, NL, TR	EN, CN, DE, FRA, IT, ES PL, RU, PT, NL, TR	EN, CN, DE, FRA, IT, ES PL, RU, PT, NL, TR	EN, CN, DE, FRA, IT, ES PL, RU, PT, NL, TR
White Balance	Auto/Manual	Auto/Manual	Auto/Manual	Auto/Manual
Gain Control	Auto	Auto	Auto	Auto
Noise Reduction	3D NR	3D NR	3D NR	3D NR



Picture Adjustment	YES	YES	YES	YES
WDR	DWDR	DWDR	DWDR	DWDR
OSD Support	YES	YES	YES	YES

General

Weatherproof Housing	YES, IP66
Anti-cut Bracket	YES, 3-Axis
Dual Voltage	NO
IR Cut Filter	YES
Heater	NO
Operation Temperature	-10°C ~ +50°C RH95% Max
Storage Temperature	-20°C ~ +60°C RH95% Max
Power Source	DC12V±10%, 500mA
Dimension	185(W) x 115(H) x 85(D)mm
Weight	500g

