

HD-TVI SPEED DOME

SCTVI-APM6A10

General Features :

6" HD-TVI Medium Speed Dome Camera
 18X Optical Zoom (f=5.35mm-96.3mm)
 1/2.8" SONY CMOS, 2.4MP/1080P
 20x6PCS+ 16x5PCS IR LEDS, IR Range: 100m
 Pan Speed: 60°/sec; Tilt Speed: 45°/sec
 Low Illumination, ICR, 3D NR,





Model	SCAPM6A10V200
Camera	
Image Sensor	1/2.8" SONY CMOS Sensor 2.4MP
Horizontal Resolution	1080P
S/N Ratio	>58db
PTZ	
Horizontal Rotation Speed	60°/s
Horizontal Rotation Range	360°
Tilt Rotation Speed	45°/s
Tilt Rotation Range	94°
Auto Flip	Horizontal 180°, Vertical 93°
Ratio Speed	Support
360° Scan	User programmable
360° Scan Speed	01-64speed setting available
A-B Scan	User programmable
A-B Scan Speed	01-64speed setting available





PWR on Action	Memory/Tour/360 scan/AB scan/Home/Nop
Park Time	1-60mins setting available
Dwell Preset	1-60s interval available
Preset Points	220
Go to Preset Speed	200°/s
Guard Tours	3 groups
Guard Points	Max.16 points, dwell time user selectable
Auxiliary Interface	
Communication Protocol	Pelco-D, Pelco-P
Communication	RS485
Baud Rate	1200/2400/4800/9600bps
General	
Operating Temperature	Indoor: 0°~ +40° Outdoor: -40°~ +60°
Operating Humidity	≤95% Non Condensing
Heater & Blower	Auto temperature control
Auto Control IR LED	PWM





OSD Menu	English
Power	DC12V/4A
IR Illumination Distance	100M
Power Consumption	≤ 36W
Lightning Protection	Transient voltage 6000V
Dimension	28x28x42(cm)
Weight	3.8kgs